

Cielo Performance 15"

All-in-One PoS terminal



Sleek, durable and fast. Cielo Performance 15" encompasses a broad range of users.

Intel Celeron™ processor, cielo performance is an elegant and fast PoS terminal.

The splash-proof unit boasts a small space saving footprint and a bright, backlit, high-resolution display ensuring ease-of-use and brilliant image quality whilst remaining power efficient.

Features

- The upright, elongated design delivers a sophisticated look which will appeal to high-end environments such as fashion outlets, restaurants, and hotels
- Cielo Performance's hardware platform can be easily upgraded by swapping out key components such as the motherboard and HDD



Specifications	
Display size / resolution	15" TFT-LCD/ 1024 X 768
Display brightness & touch screen	250 cd/m ² (CCFL); 5-Wire Resistive Touch 350 cd/m ² (LED) with Tempered Glass; Projective Capacitive Touch
Processor	Intel Celeron™ G540
System memory	2GB Standard, Maximum 4GB (1x204-pin DDR3)
Storage device	1 x 2.5" SATA HDD 320GB*
Chipset	Intel H61
Speaker	Internal Speaker 2W x 2
Construction	Aluminium Die-casting + Plastic + Glass
Housing colour	Black or White
Power supply	90W (12V / 7.5A) External Power Supply
Operating system	Windows XP, POSReady 2009, Windows 7, POSReady 7, Linux
Unit Dimensions (W x H X D)	367 x 352 x 223 mm
EMI / Safety	CE, FCC Class A
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-10°C - 55°C (14°F - 131°F)
I/O Ports	
Serial Ports	4 x External: COM1, COM2 (DB9), COM3, COM4 (RJ-45)
USB Port	5 x External (4 Rear + 1 Side)
Cash Drawer Port	1 x RJ11 (12V)
LAN Port	1 x RJ45 Gigabit
Audio Port	1 x Line Out
VGA Port	1 x VGA (HD15)
DC Output	1 x 12V DC Jack 2.5mm
Powered USB	1 x 24V Rear
Optional Peripherals	
Magnetic Stripe Card Reader	Integrated MCR Module (Single / Dual / Triple Track Selectable)
2nd Display	Integrated 11.6" or 15" LCD Display (Touch Screen Optional)
Customer Display	Integrated LCM / VFD Customer Display
Wireless LAN	Integrated 802.11 b/g/n Wireless Module
Identification Devices	RFID 13.56 MHz / Fingerprint Reader / i-Button

