

# Cielo Customer Display Range

The Cielo customer display range consists of slim and sleek, high-resolution monitors that can integrate with a diverse array of POS systems. With a variety of mounting options available, the Cielo range is versatile and can adapt to your unique in-store requirements.

### Features

- Bezel-free, high-resolution screens
- Projective Capacitive Touch (PCAP) variants available
- Optional integrated peripherals on 12" and 15" displays – including MSR, RFID, Fingerprint and iButton
- VGA and DVI output available
- Range of mounting options – including standalone, pole mounts and brackets

Cielo 11" Customer Display



Cielo 11" Customer Display	
Viewable Size Image	11.6"
Touch Screen	Glass (non-touch)
Resolution	1366 (W) x 768 (H)
Contrast Ratio	300:1
Display Colour	262K (6-bit)
Brightness (cd/m <sup>2</sup> )	200 cd/m <sup>2</sup> (LED)
MTBF	10K
Signal Connector	VGA
On Screen Display (OSD)	Menu, Up, Down, Power, Auto
Power Source	AC100 ~ 240V
Dimension (mm)	320 x 210 x 32.6

Cielo 12" Customer Display



Cielo 12" Customer Display			
Viewable Size Image	12.1"		
Touch Screen	Glass (non-touch or resistive touch)		
Resolution	800 (W) x 600 (H)	1024 (W) x 768 (H)	
Contrast Ratio	800:1	550:1	
Display Colour	16.7M		
Brightness (cd/m <sup>2</sup> )	330 cd/m <sup>2</sup> (LED)	450 cd/m <sup>2</sup> (LED)	500 cd/m <sup>2</sup> (LED)
MTBF	50K	100K	60K
	Sharp	Mitsubishi	Mitsubishi
Signal Connector	VGA or DVI		
On Screen Display (OSD)	Menu, Up, Down, Power		
Power Source	DC 12V 4.16A 50W		
Dimension (mm)	308 x 248 x 39.7		
Additional Options	Internal Speaker 2W x 2		
	MSR/RFID/Fingerprint/iButton		

Cielo 15" Customer Display



Cielo 15" Customer Display				
LCD Display Size	15" TFT LCD			
Resolution	1024 (W) x 768 (H)			
Display Colour	16.2M			
Touch	Touch		Non-Touch	
	PCAP (Tempered Glass)	5W Resistive	N/A	
Panel/Brightness	LED 350 nits	CCFL 250 nits	LED 450 nits	CCFL 250 nits
Backlight MTBF	50K hours	30K hours	100K hours	30K hours
Signal Connector	VGA			
Dimension (mm)	367 x 326 x 188			
Power Supply	50W (12V/4.16A) External Power Adaptor/Cable DC PLUG/Power 12V USB			
Additional Options	MSR/Rfid/Fingerprint/iButton			



Box Technologies Head Office  
 20 Thame Park Business Centre  
 Wenman Road  
 Thame, OX9 3XA  
 United Kingdom  
 T: +44 (0) 1844 264 000  
 E: sales@boxtechnologies.com

Box Technologies Sweden  
 Upplagsvägen 1, 4 tr  
 117 43 Stockholm  
 Sweden  
 T: +46 (0) 8 120 80 320  
 E: sales@boxtechnologies.se

Box Technologies Norway  
 Torgbygget  
 Nydalsveien 33  
 0484 Oslo  
 T: +47 22 18 26 35  
 E: sales@boxtechnologies.se