


KPC6 Series

Embedded edge PC for any application




Meet the KPC6. However it's used – kitchen management, digital signage, industrial control, back office PC or as a self-service compute module – its wide range of I/O and unrivalled reliability make it perfect for any project, even in the harshest environments, and its compact design ensures it can fit comfortably in locations with limited space.


System

 **Motherboard**
D36 / D86U

 **Storage**
2.5" SATA SSD

 **Processor**
D36: Intel Celeron J1900
D86U: Intel Skylake i5-6200U

 **Memory**
D36: 4GB RAM
D86U: 8GB RAM

 **Supported OS**
Win 7, Win 8.1, Win 10,
Linux



Certification

 **CE Mark**
Class A

 **FCC**
Class A

 **LVD**

Protecting the planet together...



Committed to
environmental
care



Environmental
Management
compliance with
ISO 14001



Community and
Social
Responsibility

Here's the detail...

System	Motherboard	D36	D86U
	Processor	Intel Celeron J1900 2.4GHz	Intel Skylake i5-6200U
	Memory	4GB RAM	8GB RAM
	Storage	2.5" SATA SSD	
	Supported OS	Windows 7, Windows 8.1, Windows 10, Linux	
I/O ports	USB	1 x USB3.0/2.0, 4x USB2.0	4 x USB3.0, 2 x USB2.0
	Serial port	3 x RJ45 (powered RS232) (COM1/2 default 5V, COM3 default 12V)	
	LAN	1 x RJ45	
	VGA	1 x DB15 female	
	Cash drawer	1 x RJ11	
	DC jack	1	
Power	Power supply	65W / 19V	90W/19V
Certificate	EMC & safety	FCC Class A / CE Mark / LVD	
Environment	Operating temperature	0°C - 35°C (32°F - 95°F)	
	Storage temperature	-20°C - 60°C (-4°F - 140°F)	
	Humidity	20% - 85°C RH non-condensing	
Weight & dimensions		222 × 138 × 36.8mm (8.7" x 5.4" x 1.4"), 1.2kg (2.6lbs)	
Mounting		100 × 100mm Standard VESA	

PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE