

### **Customer Engagement Specialists**









## Box POS135

#### **Product Overview**

Designed to operate in conjunction with modular systems or as a standalone secondary display, the POS135 monitor utilises the latest touch panel technology to provide a highly responsive, space-saving solution.

The POS135 combines a bright, bezel-free 15" LED display with tried and tested PCAP touch panel technology to deliver a sleek user experience at the point of service. The touch monitor also features an array of I/O ports for additional connectivity requirements, and a range of peripheral options to further enhance functionality.

The form factor and weight of the POS135 also comfortably lends itself to flexible mounting options, utilising the VESA 100 x 100 fitting that comes as standard on the rear of the unit.

#### **Features**



Bright, 15" LED PCAP touch panel



Slim, compact form factor



Additional connectivity available through I/O interface



Range of integrated peripheral options



Flexible mounting options

POS135		
Touch Panel	Screen Size/Type	15" LED
	Touch Screen	P-CAP Touch
	Brightness	>300 nits
	Tilt Adjustment	0° ~ 90°
	Resolution	1024 x 768
I/O Ports	USB	1 x USB 2.0 (Type A), 1 x USB 2.0 (Type B to PC) Optional – additional USB 2.0 (Type A)
	VGA	1 x DB15
	OSD Button	2 (Power, Auto)
	Audio + COM (optional)	1
	Display Port (optional)	1
	DC Jack	1 x 2 pin
Power	Power Adapter	36W / 12V
Peripherals (Optional)	MSR	3-Track MSR (USB)
	iButton	iButton (USB)
	Fingerprint	Fingerprint Reader (USB)
	Customer Display	2 x 20 Characters LCM Display (USB)
Certificate	EMC & Safety	FCC Class A, CE Mark, LVD
Environment	Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 85% RH non-condensing
Weight and Dimensions	Weight (kg)	4.8kg (10.5lbs)
	Dimensions (W x H x D)	360 x 318 x 210mm
Mounting	VESA Type	VESA Mount 100 x 100
Stands	Stand Options	Fixed Stand as standard, optional
Operating Systems	Supported OS	All variants of: Windows 7, Windows 8.1, Windows 10, Linux







# **₿** BOXTEC

Box Technologies Head Office T: +44 (0) 1844 264 000 E: sales@boxtechnologies.com

Box Technologies Sweden T: +46 (0) 8 120 80 320 E: sales@boxtechnologies.se

Box Technologies Norway T: +47 22 18 26 35 E: sales@boxtechnologies.se

BT04-BRC-P135-01