

POS337N2

Uncompromised value

We designed the POS337 with customer engagement at its core, bringing together the latest advancements in POS technology to create a highly versatile and affordable system.

Derived from the POS335, our most popular product which has been the backbone of our POS offering for over a decade, the POS337 brings an industry trusted product back to the forefront of retail technology.








System

-  **Motherboard**
Intel® Celeron J6412 (Elkhart Lake)
-  **Storage**
128GB M.2
-  **Memory**
4GB RAM



Peripherals

-  **MSR**
3-Track MSR (USB)
-  **iButton**
iButton (USB)
-  **Fingerprint**
Fingerprint reader (USB)
-  **2nd display**
11" PCAP touch (FeDP)
-  **Customer display**
2 × 20 LCM (USB)

Protecting the planet together...



Committed to environmental care



Environmental Management compliance with ISO 14001



Community and Social Responsibility

Here's the detail...

System	Processor	Intel® Celeron J6412 (Elkhart Lake)
	Memory	4GB RAM
	Storage	128GB SSD
	Supported OS	All variants of: Windows 10, Linux
I/O ports	USB	2 x USB 3.0, 2 x USB 2.0, 2x USB-C*
	Serial port	2 x RJ45 Serial (Powered RS232)
	LAN	1 x RJ45
	Cash drawer	1 x RJ11
	Video	1 x Flytech FeDP
	DC jack	1 x 4 pin w/lock
Audio	Speaker	2 x 2W
Display	Size & resolution	15.6" LED 1920×1080 HD
	Touch screen	True-Flat PCAP multi-touch
Power	Power supply	65W/19V
Certificate	EMC & safety	FCC Class A, CE Mark Class A, LVD, UKCA
Environment	Operating temperature	0°C ~ 35°C (32°F ~ 95°F)
	Storage temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 80% RH non-condensing
Weight & dimensions	Weight	5kg (11lbs)
	Dimensions (W x H x D)	369 × 310 × 230mm
Mounting	VESA	100 × 100
Stand	Fixed stand (cable management & screen tilt functionality)	

PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE