

POS350


Enhanced customer engagement

Driven by customer and partner feedback, we discovered the perfect opportunity for innovation: the need for an “ultimate product” that could deliver cutting edge POS customer engagement while still providing the reliability, ergonomic experience and technology performance required.






The result? An industry first. Our R&D teams created a feature rich, fully interactive customer engagement hub that offers data input, loyalty redemption, promotional advertising and customer identification.



System

-  **Motherboard**
Intel® Celeron J1900 (Baytrail)
Intel® Core™ i5-6200U (Skylake)
-  **Storage**
128GB SSD
-  **Memory**
up to 8GB RAM

Peripherals

-  **MSR**
3-Track MSR (USB)
-  **iButton**
iButton (USB)
-  **Fingerprint**
Fingerprint reader (USB)
-  **2nd display**
10.1" non-touch
-  **Customer display**
2 × 20 LCM (USB)



Protecting the planet together...



Committed to
environmental
care



Environmental
Management
compliance with
ISO 14001



Community and
Social
Responsibility

Here's the detail...

System	Motherboard	D36	D86U
	Processor	Intel® Celeron J1900 (Bay Trail)	Intel® Core™ i5-6200U (Skylake)
	Memory	4GB DDR4	8GB DDR4
	Storage	128GB SSD	
	Supported OS	Windows 10 IoT, Linux	
I/O ports	USB	4 x USB 2.0 1 x USB 3.0	2 x USB 2.0 4 x USB 3.0
	Powered USB	1 x 12V, 1 x 24V	
	Serial port	3 x RJ45 COM (COM1 & COM2 with 5V, COM 3 with 12V, BIOS selectable)	
	LAN	1 x RJ45	
	Cash drawer	1 x RJ11 (12V / 24V BIOS selectable)	
	DC jack	1	
Audio	Speaker	1 x 2W (optional)	
Display	LCD size	15.1"	
	Brightness (cd/m ²)	250 nits	
	Resolution	1024 x 768	
	Touch screen	True-Flat P-CAP or resistive touch	
Power	Power supply	120W/19V (with 12V/24V DC powered USB)	
Certificate	EMC & safety	FCC Class A, CE Mark Class A, LVD	
Environment	Operating temperature	0°C ~ 35°C (32°F ~ 95°F)	
	Storage temperature	-20°C ~ 60°C (-4°F ~ 140°F)	
	Humidity	20% ~ 85% RH non-condensing	
Weight & dimensions	Weight	6.75kg	
	W x D x H	365 x 348 x 294 mm	

PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE